CO₂ transfer and filling units

100/D3 SODA series

For filling cartridges and small cylinders for water gasification.



Description

The 100/D3 SODA series allows to transfer the CO2 from standard cylinders to small cylinders used for water gasification, or to cartridges and cylinders up to 5 kg.

With the 100/D3 SODA TH version, equipped with dual-speed motor, it is possible to fill cylinders with capacities between 5 and 12 kgs, with the help of an additional scale (not included in the standard equipment).

Advantages

The 100/D3 SODA series includes complete filling / weighing stations for a wide range of cylinders used for water gasification.

One of the most important features of this equipment is the integrated control scale, which is highly precise, trustable and easy-to-

| MODEL | 100/D3 SODA | 100/D3 SODA | 100/D3 SODA TH |
|-------------------------|-----------------------------|-------------|----------------|
| | SINGLE PHASE | THREE-PHASE | THREE-PHASE |
| FLOW-RATE (kg/h) | ~ 180 | | 180 / 360 |
| VOLTAGE/FREQ. (Vac/Hz) | 230/50 | 400/50 | 400/50 |
| POWER (kW) | 1,5 | | 1,5 |
| DIMENSIONS (Lxlxh) (mm) | 950x550x1150 | | 950x550x1150 |
| SCALE FLOW-RATE (kg) | 25 | | 25 |
| DIVISION (g) | 2 | | 2 |
| WEIGHT (kg) | 130 | | 130 |
| CODE | MCBE250-U-LM MCBE250-A-LM | | MCBE255-A-LM |



CO₂ transfer and filling units





Filling head with automatic locking SPK Quick

Components and devices

- > Liquid CO2 volumetric pump with:
 - Three ceramic pistons
 - Belt and pulleys driven
 - Brass head
 - Stainless steel valves
 - Cylinder pressure relief valve
 - Control gauge and maximum pressure switch
- > Integrated electronic scale with:
 - Automatic stop at required filling weight
 - Digital display
 - Max load 25 kg., accuracy 2 g.
- > Clamping device for "SODA" type cylinders equipped with quick coupling
- > 24V electrical panel board



Standard equipment:

| DESCRIPTION | CODE |
|---|-------------|
| PTFE inlet hose AISI 304 stainless steel, length 2.000 mm with source | MCB/MAD01 |
| cylinder connector | |
| PTFE purge hose AISI 304 stainless steel braided, length 1.700 mm | MCB/MAN02 |
| Use and maintenance manual | |
| Options on request: | |
| DESCRIPTION | MODEL |
| Filling head with automatic locking SPK Quick | ACBE030/002 |
| Adapter with manual clamp for filling cylinders on integrated scale - SPK Quick | ACB/AMR15 |
| Adapter with manual clamp for filling cylinders on integrated scale | ACB/AMR11 |
| Extra electronic scale to be positioned on the floor | |
| Manual vice for scale installation on scale | VIF/BIL |
| Manifold to connect 2 source cylinders C2BB | RGFN200 |
| Manifold to connect 3 source cylinders C3BB | RGFN205 |
| Manifold to connect 4 source cylinders C4BB | RGFN210 |
| Rack for holding 2 source cylinders R2BB | RGFN300 |
| Rack for holding 3 source cylinders R3BB | RGFN305 |
| Rack for holding 4 source cylinders R4BB | RGFN310 |
| Refrigerator cell to maintain n°1 source cylinders at controlled temperature | MCBE101 |
| Adapters on request | |

PER MAGGIORI INFORMAZIONI:

> FOR FURTHER INFORMATION CONTACT:
POUR INFORMATIONS CONTACTED:

