

# Wall ramp for cylinder testing

## HT model

Highest quality and performance



### APPLICATIONS

The ramp is specifically designed to achieve the testing of cylinders / reservoirs safely and efficiently. Suitable to test 1 to 10 cylinders depending on the customer needs, it is conceived for wall mounting.

### TECHNICAL SPECIFICATIONS

- Stainless steel support
- High pressure manifold
- High pressure shut off ball valves
- Flexible hoses for cylinder connection
- Fast connection for cylinder testing (on request)
- Control gauge 0 ÷ 600 bar
- Conformity certificate
- Use and maintenance manual

## Wall ramp for cylinder testing



HT ramp – 1 place



HT ramp – 3 places

### TECHNICAL FEATURES

#### HT MODEL – CODE: MZCZ025

- Available for 1 – 10 cylinder testing places
- Total min. dimensions: 600 / 340 / 400 (h) mm
- Total max dimensions: 3300 / 340 / 400 (h) mm
- Max service pressure: 500 bar
- Higher service pressures on request

> PER MAGGIORI INFORMAZIONI:  
> FOR FURTHER INFORMATION CONTACT:  
> POUR INFORMATIONS CONTACTER:

**DAMOTEK S.r.l.**

Via Avv. Giovanni Agnelli, 10 12033 MORETTA (CN) ITALY  
Tel: +39 0172 911235  
Fax: +39 0172 911322

[www.damotek.com](http://www.damotek.com)  
[info@damotek.com](mailto:info@damotek.com)



ISO 9001